



# GP Submersible Groundwater Pumps

Ground water pump for water testing



- Used and trusted in the groundwater industry for more than 15 years
- Recommended by drillers, hydrologists and field technicians
- Practical for dedicated use and disposal
- Reduces labor costs and saves time

## Description

Global Water's groundwater pumps provide an easy-to-use, high-quality, economical solution for purging, ground water testing, and well development to a depth of 60ft (18m). The submersible groundwater pump's 1 5/8" (40mm) diameter is ideal for use in 2" or larger monitoring wells. Each groundwater pump is self priming when fully submersed and can be connected directly to a DC power source to begin pumping. All Global Water groundwater pumps are tough and powerful with plastic construction and a stainless steel impeller. The groundwater pumps can pump up to 3 US gallons (11.4 ltrs) per minute. These groundwater pumps have been used and trusted within the groundwater industry for more than 15 years and are recommended by drillers, hydrologists and field technicians around the world.

## Specifications

*Voltage:*

GP1352 & GP1652: 12V DC

GP1354: 24V

*Fuse size:* 3-5Amps

*Hose:* 3/8" or 1/2"

*Max Head Height:*

GP1352 & GP1354: 30ft

GP1652: 60ft

*Material in contact with liquid:*

Pump Body: ABS, Seals: Nitrile, Strainer: Polypropylene,

Impeller: Stainless Steel/PBT, Cable: PVC

*Dimensions:* 5-1/16 X 1-7/16 in (129 X 36 mm)

*Weight:* 0.3lbs (0.15kg)

*For more specifications please visit [www.globalw.com](http://www.globalw.com)*

## Options and Accessories

Call us or see the website, [www.globalw.com](http://www.globalw.com) for pricing information.

Inline pumps to boost pumping distance. See website for more information.

