

TC-3000 Tri-Meter

Measure Turbidity, Color, & Chlorine in one meter



- Meets ISO 7027/EPA 180.1 for Turbidity Meters
- Low Level Detection of Turbidity, Chlorine, and Color
- Programmable Auto-Shut Off
- Log up to 4000 time and date stamped recordings
- Supports Six Languages

Specifications

Turbidity:

Unit of Measure: NTU, FNU, FAU, ASBC, & EBC

Range: 0-4000

Resolution: 0.01 NTU/FNU (0.00-10.99)
0.1 NTU/FNU (110-4000)
1 NTU/FNU (110-4000)

Reproducibility: 0.02 NTU/FNU, 0.5 FAU

Chlorine:

Range: 0-10 ppm

Resolution: 0.01 ppm (0-5)
0.1 ppm (5-10)

Color:

Range: 0-500 CU (color units)

Resolution: 0.1 CU (0-100 CU)
1 CU (100-500 CU)

Light Source: 860nm LED (ISO)/Tungsten (EPA), 525 nm LED, UV LED 375

Accuracy: ± 2%, 0.02 or ± 2%, ±0.5 CU or 2%

Detection Limit: 0.05 NTU/FNU, 0.02 ppm, 0.2 CU

Signal Averaging: Disabled, 2, 5, 10

Power: 9V Battery, AC Optional

Data Logging: 4000 points

Auto Shut-off: Disabled, 5, 10, 30

Response time: <5 s

Languages: English, French, Spanish, Japanese, Italian, & Portuguese

Size: 8-7/8"x4-5/8"-1-7/16" (226mmx117mmx36mm)

Weight: 3 lbs (1250g)

Description

The TC-3000 Tri-Meter is ideally suited for both low-level drinking water applications as well as monitoring high turbidity in the field. The Tri-Meter has a six-detector design with special focusing optics allowing for long-term stability over a wide range of operational conditions. The Tri-Meter uses the unique detector arrangement to measure Turbidity, Color, and Chlorine. The Tri-Meter comes in two designs: one with a tungsten lamp to meet EPA 180.1 specifications, the other comes with a IR LED emitter and meets the ISO 7027 standard. The Tri-Meter uses a tube-positioning ring to limit tube variability enabling maximum sensitivity and accuracy.

The TC-3000 Tri-Meter uses an advanced micro controller which allows for advanced calibration algorithms and support of up to 6 languages including English, French, Spanish, Japanese, Portuguese, and Italian. The instrument can record up to 4000 time and date stamped data points. The Tri-Meter is compatible with Smart Link 2 software allowing the unit to interface with a PC and download data for analysis. The Tri-Meter has an easy to use menu driven system displayed on an easy to read graphic LCD display.



Options and Accessories

TC-3000e Tri-Meter, EPA Version

Includes 0, 1, and 10 NTU standards, sample bottle, 4 sample tubes, DPD tablets, and extra battery.

TC-3000i Tri-Meter, ISO Version

Options

AC adapter

SMARTLink 2 Software

Liquid DPD 1A Reagent, 60mL

Liquid DPD 1B Reagent, 60mL

Liquid DPD 3 Reagent, 60mL

NOTE: DPD 1A and DPD 1B are both required to test free residual chlorine and DPD1A, DPD1B and DPD3 are required for testing total residual chlorine.

Contact
Global Water
for all your
instrumentation
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



Global Water

The Leader in Water Instrumentation

In the U.S. call toll free

at 1-800-876-1172

International: 916-638-3429

Fax: 916-638-3270

Email: globalw@globalw.com

Visit our online catalog at:

www.globalw.com

Our Address:

11390 Amalgam Way

Gold River, CA 95670