

## W-23XD Water Quality Sonde

Water quality instrumentation for simultaneously measuring up to 13 different parameters



- Handheld water quality monitoring system with water quality sonde
- Rugged, fully submersible sonde
- Monitor up to 13 different parameters simultaneously
- Dry cell batteries
- Built in datalogger
- Ideal for multi-parameter water quality measurements without having a permanent installation

### Description

Global Water's W-23XD water quality sonde brings laboratory accuracy and the ease of push-button operation to water quality instrumentation measurement in the field. Years of water quality instrumentation technology development have resulted in the form of a 97-mm diameter water quality sonde: a compact water quality instrument able to offer high pressure tolerance, long-term continuous measurement capability and highly accurate for the simultaneous monitoring of up to 13 parameters. The water quality sonde can simultaneously measure: pH, temperature, dissolved oxygen, conductivity, salinity, turbidity, total dissolved solids (TDS), water depth, oxidation reduction potential (ORP), seawater specific gravity and up to three specific ions. Featuring a powerful water quality sonde and state-of-the-art functions, the water quality instrumentation makes it easy to get highly reliable water quality data simply and quickly just by submersing the sensor in the water. The water quality sonde is flexible enough to use for checking the quality of a broad range of water samples, from factory effluent to urban drainage, river water, lake and marsh water, aquatic culture tanks, agricultural water supplies, and seawater. The water quality instrumentation is water resistant, so it can be used safely even in the rain.

### Specifications

**Range:**

- PH- 0-14 with 0.01 pH resolution and  $\pm 0.1$ pH accuracy
- DO- 0-20 mg/L with 0.01 resolution and  $\pm 0.2$  mg/L accuracy
- Conductivity-0-10 S/m with 0.1% FS res. and  $\pm 3\%$  accuracy
- Salinity- 0-4% with 0.01% resolution and  $\pm 0.3\%$  accuracy
- Temp- 0-55C with 0.01° C resolution and  $\pm 1.0$ ° C accuracy
- ORP-  $\pm 1999$  mV with 1mV resolution and  $\pm 15$ mV accuracy
- Turbidity- 0-800 NTU with 0.1 NTU res.  $\pm 5\%$  accuracy
- Seawater Specific Gravity- 0-50 $\sigma$ t with 0.1 $\sigma$ t res. and  $\pm 5\%$  $\sigma$ t accuracy
- TDS- 0-100 g/L with 0.1% FS resolution and  $\pm 5$ g/L accuracy
- Water Depth- 0-100 m with 0.1 m res. and  $\pm 5\%$  accuracy
- Ion- 0.1% FS resolution and  $\pm 10\%$  accuracy

Visit [www.globalw.com](http://www.globalw.com) for more specifications

### Options and Accessories

**W-23XD Water Quality Sonde**

Included detachable 2m cable, control unit, sonde, pH and Do sensors, carrying case. ION SENSORS ARE NOT INCLUDED.

Additional cable lengths available for W-23XD, please see our website, [www.globalw.com](http://www.globalw.com).

**ION Sensors**

- Nitrate
- Chloride
- Calcium
- Fluoride
- Potassium
- Ammonia

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



**Global Water**  
The Leader in Water Instrumentation

In the U.S. call toll free  
at 1-800-876-1172  
International: 916-638-3429  
Fax: 916-638-3270  
Email: [globalw@globalw.com](mailto:globalw@globalw.com)

Visit our online catalog at:  
[www.globalw.com](http://www.globalw.com)  
Our Address:  
11390 Amalgam Way  
Gold River, CA 95670